



# ColorPak

Blended Dry Pigments for Coloring ColorTek Exterior Stucco



## Packaging

1lb (454g) to 2.8lb (1270g) paks

## Storage

1. Store containers in a cool, dry location.
2. Store away from direct contact with the ground and/or concrete.
3. Store out of direct sunlight.
4. Protect containers from weather and other damage.

## Shelf Life

1 year

## Color

Available in a wide variety of colors. See the most current Omega Color Chart for stock colors available.

## Product Description

**C**olorPak is a dry blended formulation of iron oxide pigments used to color ColorTek Stucco.

## Features

*Field Tinting*

*Flexible*

## Benefits

No inventory of pre-mixed material required.

Can be used with a variety of products

## Basic Uses

ColorPak is intended for coloring ColorTek stucco.

## Area of Use

ColorPak may be used to color the following products:

1. ColorTek Exterior Stucco
2. ColorTek SmoothCoat Exterior Stucco

**NOTE:** Adding ColorPak to materials other than those listed will not produce the same colors. The color choice will determine the required ColorTek Base designation and should be properly coordinated.

## Mixing

1. Add the appropriate number of ColorPak containers to the water in the mixer prior to adding ColorTek Stucco.
2. Mix for 2 to 3 minutes or until completely blended.
3. Continue with ColorTek mixing instructions.

**WARNING:** Colors may vary do to climatic conditions, method of application, over or under mixing, etc.

**NOTE:** Ensure ColorPak is used with the proper base (refer to ColorTek Color Chart)

## Limitations

**DO NOT** add any other materials to the mixture of the product without written approval from Omega Products International.

**DO NOT** deviate in the mixing or application procedures contained in this, or any other Omega Product Data Sheets, without written approval from Omega Products International.

**DO NOT** add any more water than prescribed.

**DO NOT** use more than one ColorPak per bag of ColorTek without approval from Omega Products International.

**DO NOT** add ColorPak to any other materials than those listed without written approval from Omega Products International, Inc.

**NOTE:** Failure to follow manufacturers written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Omega Products International we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process. See Omega Products International's Technical Bulletin OP813 on Jobsite Mockups. It is expressly understood and agreed that color, texture and pigment

streaking variations are inherent in all integral colored products and these conditions are not considered defects.

## Cleaning

Cleaning may be accomplished with water immediately after use. Dry powder should be vacuumed or swept up.

## Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

**KEEP OUT OF REACH OF CHILDREN**

www.omega-products.com

### Disclaimer

Omega Products International [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of

Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

### Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

### Technical Assistance

Technical assistance and information is available by calling Omega Products International at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at [info@omega-products.com](mailto:info@omega-products.com).

### Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.