



# E-FX Admix

An Efflorescence Reducing Admixture



## Packaging

4 fl oz (118mL) bottles  
1 Gallon (3.8L) jugs

## Storage

1. Store bottle in a cool, dry location.
2. Store at a temperature below 90°F (32°C).
3. Store out of direct sunlight.
4. Protect from weather and other damages.

## Shelf Life

Minimum of 1 year.  
Depending on storage conditions, the shelf life may be greater than stated

## Color

Milky light-brown

## Product Description

**E**-FX Admix is designed to help reduce efflorescence and improve the performance in approved cement-based products. When added to the material, E-FX Admix will offer long lasting protection from the elements while retaining the surface's natural appearance and vapor permeability.

## Features

## Benefits

<i>Efflorescence Control</i>	Reduces the frequency and quantity of efflorescence
<i>Freeze-thaw Durability</i>	Helps to improve durability against freeze-thaw cycles; thereby lengthening substrate life and reducing maintenance costs
<i>Pre-Measured Packaging</i>	Easy to use, it will save time and labor
<i>Natural Finish</i>	It will not alter the natural look of the finish
<i>Highly Vapor Permeable</i>	Allows substrate to naturally breath

## Basic Uses

E-FX Admix is added to fog coat, stucco and similar products to reduce efflorescence and improve performance.

## Area of Use

E-FX Admix may be added to the following products:

1. OmegaCoat
2. Fog coat products
3. ColorTek Stucco
4. Cement-based stucco products
5. Other approved cement-based products

## Mixing

### Priming the Pump:

When using the 1-gallon jug of E-FX Admix with the supplied pump, the pump must be primed prior to use to ensure accurate dosage. To prime the pump, fully depress the pump repeatedly until the full 1 oz (30 ml) dosage of E-FX Admix is dispensed in a single pump. It may take up to four depressions until the pump is fully primed.

### Adding the E-FX Admix:

1. Shake E-FX Admix jug or bottle thoroughly prior to use. If using the pump, ensure it is primed by following the instructions above.
2. Add the volume per Table 1 of E-FX Admix to the product's water and thoroughly mix.
3. Follow the applicable product data sheet's application instructions.

### Notes:

1. When E-FX Admix is used in the stucco finish and fog coat is then applied, add 4 oz (one bottle) of E-FX Admix to each bag of fog coat.
2. If the whole bag of product is not going to be used, use only the proportional amount of the admix.
3. Contact Omega Products for use in other products.

THIS PRODUCT IS NOT TO BE DILUTED.

Table 1

Omega Product (Generic Equivalent)	Volume of E-FX	No. of Pumps	No. of Bottles
ColorTek (Cement-based stucco finish) 90 lb bags	4 oz (120 ml)	4	1
OmegaCoat (Fog Coat) 25 lb bags	4 oz (120 ml)	4	1
Super Cement (Plastic or common cement) 94 lb bags	20 oz (590 ml)	20	5
Diamond Wall (One coat stucco) 80 lb bags	14 oz (414 ml)	14	3.5
Sanded Super Cement (Pre-sanded scratch and brown) 80 lb bags	4 oz (120 ml)	4	1
Sanded Diamond Wall (Pre-sanded one coat stucco) 80 lb bags	4 oz. (120 ml)	4	1
Siena Type S or SVM Mortars (Type S or similar mortars) 94 lb bags	4 oz (120 ml)	4	1

## Limitations

**DO NOT** allow material to freeze. Material that is allowed to freeze may suffer irreparable damage.

**DO NOT** add any other materials to the mixture of the product without written approval from Omega Products International.

**DO NOT** deviate in the mixing or application procedures contained in this, or any other Omega Product Data Sheets, without written approval from Omega Products International.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

## Cleaning

Cleaning may be accomplished with water immediately after use.

## Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

**KEEP OUT OF REACH OF CHILDREN**

www.omega-products.com

### Disclaimer

Omega Products International [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufac-

turer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product

for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

### Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect.

For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

### Technical Assistance

Technical assistance and information is available by calling Omega Products International at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

### Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.

E-FX ADMIX