## AkroFlex EIFS Sealants

## Approved Sealants for use with AkroFlex EIF Systems

Omega Products International, Inc. requires that sealants used with our AkroFlex EIF Systems meet the following criteria:

- Type S or M, minimum Grade NS, minimum Class 25, and Use O sealant complying with ASTM C 920. Under the Use O classification, the sealant must be qualified for each material to which the sealant will be applied.
- 2. The sealant manufacturer must approve the products use with EIF systems.

Based on the above criteria, Omega Products approves the use of the following sealants with the AkroFlex EIF Systems:

- · Dow Corning 790
- Dow Corning 795
- · GE SCS 2700 series SilPruf LM
- Pecora Dynatrol 1
- Sika Sikaflex 1A / 15LM
- · Tremco Spectrum 3
- · BASF Masterseal NP 100
- BASF Masterseal NP 150

These sealants should be applied according to the sealant manufacturer's specifications. If the above sealants are not available, submit an alternate sealant request in writing to Omega Products International for approval.



## Disclaimer

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANT-ABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condi-

tion of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually prowen to be defective. Handling and use of the products are beyond the control of Manufacturer, therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the

product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buwes

## Technical Assistance

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at "info@omega-products.com".

